

ARDEX BR 340

STRUCTURAL CONCRETE PATCHING AND REPAIR MORTAR



ARDEX BR 340 Structural Concrete Patching and Repair Mortar is designed for reinstating concrete surfaces damaged through concrete spalling and other chemical or mechanical causes. ARDEX BR 340 is a high-build patching mortar and is capable of being applied up to a thickness of 80mm on vertical, horizontal and overhead surfaces.

- MICROTEC® Fibre reinforced
- Polymer modified
- Shrinkage compensated
- Contains active corrosion inhibitor
- Low Resistivity (<math><10,000\Omega\text{cm}</math>)
- Used in conjunction with ARDEX BRX 60 LO Low Output Anodes
- Good adhesion to concrete
- Meets or exceeds Class R3 of EN 1504

Location

- Internal or external
- Vertical, horizontal, or overhead

Set times

- Pot life: 30 - 45 min
- Initial set: 45 - 60 min
- Final set: 60 - 90 min

Coverage

- 1.25m² at 10mm thick per 20kg bag

System Components

- Primer & Additive: ARDEX WR Prime
- Bonding Bridge: ARDEX BRP 30 EP
- Zinc Primer: ARDEX BR 10 ZP
- Sacrificial Anodes: ARDEX BRX 60 LO

Packaging

20kg bag

Code

24611



To find out more call 0800 227 339
or visit www.ardex.co.nz

